

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C07D 487/00	A2	(11) International Publication Number: WO 00/52011 (43) International Publication Date: 8 September 2000 (08.09.00)
<p>(21) International Application Number: PCT/US00/03784</p> <p>(22) International Filing Date: 15 February 2000 (15.02.00)</p> <p>(30) Priority Data: 60/120,187 16 February 1999 (16.02.99) US</p> <p>(71) Applicant: CORDANT TECHNOLOGIES, INC. [US/US]; Suite 1600, 15 West Temple, Salt Lake City, UT 84101-1532 (US).</p> <p>(72) Inventors: SANDERSON, Andrew, John; 2711 North, Mountain Road, North Ogden, UT 84414 (US). WARNER, Kirstin; 1175 Canyon Road #59, Ogden, UT 84404 (US). WARDLE, Robert, B.; 1630 North, 1770 East, Logan, UT 84321 (US).</p> <p>(74) Agents: COLTON, Kendrew, H. et al.; Pillsbury Madison & Sutro, LLP, 1100 New York Avenue, NW, Washington, DC 20005 (US).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>Without international search report and to be republished upon receipt of that report.</i></p>
<p>(54) Title: PROCESS FOR MAKING 2,4,6, 8,10,12- HEXANITRO- 2,4,6,8,10, 12- HEXA AZATETRACYCLO [5.5.0. 0^{5,9}.0^{3,11}] -DODECANE</p>		
<p>(57) Abstract</p> <p>In this process 2,6,8, 12-tetraacetyl- 2,4,6,8, 10,12-hexaazatetracyclo- [5.5.0.05, 903,11]-dodecane ("TADH") is subjected to nitrolysis in the presence of a mixed acid to form HNIW. The mixed acid comprises at least one nitronium ion source (preferably nitric acid) and at least one strong acid (preferably sulfuric acid) capable of generating a nitronium ion from the source. The ratio of nitronium ion source to strong acid and the amount of TADH used are selected so that, in the event that the nitrolysis reaction is carried out at 85 °C, 99 % nitramine conversion will occur within ten minutes.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**PROCESS FOR MAKING
2,4,6,8,10,12-HEXANITRO-2,4,6,8,10,12-
HEXAAZATETRACYCLO[5.5.0.0^{5,9}.0^{3,11}]-DODECANE**

5

10


BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to a process for making 2,4,6,8,10,12-hexanitro-
15 2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]-dodecane, also commonly
known as 2,4,6,8,10,12-hexanitro-2,4,6,8,10,12-hexaazaisowurtzitane, HNIW
or CL-20, and in particular relates to a continuous process for making HNIW.

2. Description of the Related Art


HNIW is a polycyclic caged nitramine oxidizer having the following
20 chemical structure:



For most existing weapons systems, the most critical ingredient in terms of propellant and explosive performance is the oxidizer. HNIW, with its substantial increase in performance output, presents significant opportunities in energy capabilities for propellant and explosive systems. It may be possible to replace existing weapons system energetic fillers with HNIW to increase shaped charge anti-armor penetration, increase missile payload velocity and standoff, increase underwater torpedo effectiveness and lethality, and improve gun propellant impetus.

In view of the potential plethora of applications for HNIW, it would be advantageous to develop a continuous process for making HNIW in high production capacities.

According to one known process for making HNIW, HNIW is synthesized via nitration of the precursor, tetraacetyldiformyl-hexaazaisowurtzitane ("TADF"), as shown below:



15

TADF can be synthesized according to the procedure described in U.S. Patent No. 5,739,325 to Wardle, entitled "Hydrogenolysis of 2,4,6,8,10,12-hexabenzyl-2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]dodecane," the complete disclosure of which is incorporated herein by reference. However, nitrolysis of TADF to form HNIW of acceptable purity has been found to

require long reaction times, such as on the order of 2 to 3 hours. Attempts to increase the kinetics of the reaction and shorten reaction times have resulted in the formation of formyl-containing impurities. Thus, it would be extremely difficult to produce HNIW of acceptable purity via a continuous process which involves the nitrolysis of TADF to HNIW, since long residence times are required for the nitrolysis of the precursor, TADF, to HNIW.


A series of acyl group-containing hexaazaisowurtzitane derivatives is disclosed in EP 0 753 519 A1, the complete disclosure of which is incorporated herein by reference. Examples 20 and 22 of this European publication collectively disclose a process in which 2,6,8,12-tetraacetyl-2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]-dodecane (also known as tetraacetylhexaazaisowurtzitane or "TADH") is, in a stepwise manner, first nitrosated with sodium nitrate and then oxidized with 100% nitric acid to form a dinitro intermediate, dinitrotetraacetylhexaazaisowurtzitane. After distilling off the nitric acid, the dinitro intermediate is reacted with a mixed acid consisting of 50 vol.% nitric acid (100%) and 50 vol.% sulfuric acid (100%) to form HNIW. However, it is reported that the second stage of the reaction took 8 hours at 0°C followed by 67 hours at room temperature to go to completion.

It would therefore be a significant advancement in the art to provide a reasonably rapid, continuous process for the formation of HNIW. In particular, it would be a noteworthy advance in the synthesis of HNIW to significantly shorten the nitrolysis of TADF or TADH to HNIW.

SUMMARY OF THE INVENTION

In accordance with the principles of this invention, the above-mentioned and other advances in the art are attained by the provision of a process in which TADF is replaced with 2,6,8,12-tetraacetyl-2,4,6,8,10,12-hexaazatetracyclo-[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("TADH"), and subjecting the TADH to nitrolysis in the presence of a mixed acid to form HNIW. The mixed acid comprises at least one nitronium ion source and at least one strong acid

(preferably nitric acid and sulfuric acid, respectively) capable of generating nitronium ions from said source. The nitrolysis reaction is shown below:



The volumetric ratio of nitronium ion source (e.g., HNO₃) to strong acid (e.g., H₂SO₄) is preferably selected so that when reacted at a temperature of 85°C, a product having undergone at least 99% conversion to nitramine is rapidly formed, preferably in no more than 10 minutes. More particularly, the volumetric ratio of HNO₃:H₂SO₄ is preferably about 7:3.

As referred to herein, the purity of the HNIW product can be rated based on a "conversion to nitramine" standard. Conversion to nitramine means 100 multiplied by the ratio of the number of available substituted and unsubstituted nitrogen groups (of the analyzed nitramines) converted to nitramine groups (N-NO₂) divided by the total number of substituted (N-R) and unsubstituted (N-H) nitrogen groups (of the analyzed nitramines) that are capable of being converted to nitramine groups. The conversion to nitramine is determined by NMR analysis as follows. Analysis of HNIW by NMR produces two peaks. The first of these peaks represents the protons at the 3, 5, 9, and 11-positions of HNIW, whereas the second of these peaks represents the protons at the 1-position and 7-position of HNIW. Generally, the first peak is approximately twice the area of the second peak, since the first peak accounts for twice as many protons as the second peak. Other nitramine impurities produced during HNIW synthesis are present during NMR analysis and produce their own distinct peaks. Nitramine conversion is determined by taking the ratio of the area of the second HNIW peak (for the

1,7-positioned protons) to the greatest area of any peak produced by protons of a nitramine other than HNIW, i.e., a nitramine impurity. Thus, a conversion to nitramine of at least 99% HNIW means that the smaller HNIW peak area of the 1,7-position protons from NMR analysis is at least 99 times the area of the peak of greatest area produced by protons of a nitramine impurity (that is, a nitramine other than HNIW).

In accordance with a preferred embodiment of this invention, the process of converting TADH to HNIW by nitrolysis with the mixed acid is conducted in a continuous manner.

These and other objects, features, and advantages of the present invention will become apparent from the following detailed description of the invention when taken in conjunction with the accompanying Figure which illustrates, by way of example, the principles of this invention.

BRIEF DESCRIPTION OF THE FIGURE

The accompanying Figure is a schematic view of a flow diagram of a continuous process for the nitrolysis of TADH to HNIW in accordance with an embodiment of this invention.

DETAILED DESCRIPTION OF THE INVENTION

As mentioned above, Examples 20 and 22 of EP 0 753 519 A1 collectively disclose a process in which TADH is selected as a precursor and, after being nitrosated and thereafter nitrated, is reacted with a mixed acid consisting of 50 vol.% nitric acid (100%) and 50 vol.% sulfuric acid (100%). However, it is reported that the mixed acid took 67 hours at room temperature to drive the reaction to completion.

Intuitively, and as dictated by known chemistry principles, it would seem that the rate of reaction would be increased by increasing the sulfuric

acid concentration of the mixed acid, since an increase in the sulfuric acid concentration generates a corresponding increase in nitronium ion activity. However, the present inventors discovered, to their surprise, that high concentrations of strong acids, such as sulfuric acid, decrease the rate of HNIW formation. High proportions of such strong acids result in impure HNIW containing acetyl substituents being quickly precipitated from the reaction mixture before completion of the nitrolysis of TADH to HNIW. Hence, subsequent nitrolysis of the precipitated, partly nitrated TADH is consequently slowed.

The present inventors found that the reaction rate for the nitrolysis of TADH to HNIW can advantageously be increased by nitrolysis of the TADH with a mixture comprising nitric acid and a strong acid, preferably sulfuric acid, at prescribed volumetric ratios. The optimum volumetric ratio of nitronium ion source to strong acid is dependent upon the nitronium ion source and strong acid selected, as well as the amount of TADH present, since the concentration of TADH affects the amount of water generated and, hence, solubility. Generally, however, a volumetric ratio of $\text{HNO}_3:\text{H}_2\text{SO}_4$ in a range of from about 6:4 to about 8:2 is preferred. At this preferred range, nitrolysis to 99% nitramine conversion can be achieved in less than 20 minutes at 85°C. (A temperature of 85°C is presented for illustrative purposes only as a control temperature at which nitramine conversion is measured as a function of time, although 85°C is particularly suitable since it drives the kinetics of the reaction without causing the acids to boil. It is to be understood that this process may be carried out at other temperatures, but preferably is carried out to have ratios of mixed acid components and ingredients selected so that, if the treatment step had been carried out at 85°C, a 99% conversion to nitramine would be obtained in not more than 10 minutes.) Most preferably, the volumetric ratio of $\text{HNO}_3:\text{H}_2\text{SO}_4$ is about 7:3, so that the reaction is capable of proceeding at 85°C to form a product of 99% conversion to nitramine (NMR) in not more than 10 minutes. Another strong acid that can be used in lieu of sulfuric acid is methylsulfonic acid $\text{CH}_3\text{SO}_2\text{OH}$, although methylsulfonic acid should be used in a volumetric ratio closer to about 7:3 to provide the

nitrolysis reaction with the capability of forming 99% conversion to nitramine at 85°C within 20 minutes.


The ratio of mixed acid (in milliliters) to TADH (in grams) is preferably at least about 7:1, can be in a range of from about 7:1 to about 30:1, more preferably is about 7.5:1 to about 10:1, and most preferably is about 8:1. At ratios less than about 7:1, the efficiency of the conversion to nitramine is adversely effected. Ratios greater than about 30:1 are discouraged for efficiency and economic reasons.

The acid mixture may contain up to about 5% by volume of water, but most preferably is substantially free of water, meaning that it has less than 2% by volume of water. More preferably, the acid mixture has less than 1% by volume of water.

The Figure depicts an exemplary continuous flow process for converting TADH to HNIW. In the illustrated process, TADH is fed through a screw feeder 10 into a first cooling vessel 12, which is preferably operated at about 0-20°C. Also fed into the first cooling vessel 12 through conduit 14 containing a condenser 15 is a mixed acid, which is introduced in the prescribed concentrations to dissolve the TADH in about 2-3 minutes. The mixed acid preferably comprises a mixture of sulfuric acid and nitric acid, added in such amounts that the volumetric ratio of $\text{HNO}_3:\text{H}_2\text{SO}_4$ is preferably about 7:3. A portion of the solution is continuously tapped off from the first cooling vessel 12 and fed through conduit 16 into a reactor 18, which contains condenser 19 and is operated at a temperature of about 85°C. The solution is maintained in the reactor 18 for a residence time of 10 minutes to form HNIW, which is removed through conduit 20 and fed into a second cooling vessel 22. Ice is fed through feeder 24 into the second cooling vessel 22 to maintain the second cooling vessel 22 at an operating temperature of about 0-20°C. The volumetric rate of the ice fed through feeder 24 is preferably equal to the volumetric rate of acid feed to the second cooling vessel 22. A product stream overflowing from the vessel 22 is filtered and collected.

TADH is available through Asahi of Osaka, Japan. As an alternative source of TADH, a process for preparing TADH will now be explained in detail. It is understood, however, that the invention is not to be restricted to this process embodiment.

- 5 TADH can be prepared from hexabenzylhexaazaisowurtzitane (HBIW) as a precursor. HBIW can be synthesized according to the procedure described by Nielsen et al. in "Polyazapolycyclics by Condensation of Aldehydes with Amines. 2. Formation of 2,4,6,8,10,12-Hexabenzyl-2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]dodecanes from Glyoxal and Benzylamines," Journal of Organic Chemistry, Vol. 55, pp. 1459-66 (1990) and U.S. Patent No. 5,723,604, the complete disclosures of which are incorporated herein by reference. It is understood, however, that equivalents of HBIW might also be used, such as precursor compounds containing substitutions for one or more of the benzyl groups.
- 10
- 15 HBIW is subjected to a hydrogenolysis step to form tetraacetyldibenzylhexaazaisowurtzitane ("TADB"), as described in U.S. Patent No. 5,739,325 and as shown below:



- In this preparatory process, a quantity of HBIW, a cosolvent, and a bromine source are placed into a reaction vessel. Representative of suitable
- 20

cosolvents are N,N-dimethylformamide ("DMF"), N-methylpyrrolidone ("NMP"), and 1,2-dimethoxyethane. Suitable bromine sources include molecules having active bromine, such as benzyl bromide, acetyl bromide, and bromine gas (Br_2). The HBIW, cosolvent, and bromine source are preferably mixed in an atmosphere which is substantially non-reactive with hydrogen. For instance, the reaction vessel can be purged with an inert atmosphere, such as nitrogen. Alternatively, the reaction vessel atmosphere can be removed by vacuum. Acetic anhydride and a palladium hydrogenolysis catalyst are added to the reaction vessel, followed immediately by introduction of hydrogen into the reaction vessel.


The hydrogenolysis catalyst is preferably added to the reaction vessel in an amount less than 10% by weight based on the HBIW substrate. Typical hydrogenolysis catalysts which can be used include $\text{Pd}(\text{OH})_2$, Pd, and mixtures thereof on carbon commonly used as a catalyst support. Several standard palladium metal and Pearlman's-type catalysts have both been found to be suitable. Such catalysts are commercially available. Similarly, catalysts that are provided either water-wet or dry have been useful. The weight percent of active palladium on carbon is preferably less than 10%, more preferably less than 5%, and can be as low as 3%.

The hydrogenolysis catalyst is preferably substantially free of water. This can be accomplished by washing the catalyst with the co-solvent prior to introduction into the reaction vessel to remove water associated with the catalyst. The palladium catalyst is normally shipped water-wet, with approximately 50% of the weight being water. While not wishing to be bound by theory, it is presently believed that acetic acid, formed by reaction of acetic anhydride in the reaction mixture with the water on the catalyst, reduces the yield and increases the chances of a failed or incomplete reaction. Previous efforts at water removal, such as vacuum drying, which was unacceptable due to fire hazard and catalyst activity reduction, or washing with acetic anhydride, did not fully remove water and left acetic acid present. Washing with the polar co-solvent effectively removes water and does not introduce deleterious side products or reduce catalyst activity.

It has been discovered that addition of the reactive acetic anhydride immediately prior to hydrogen introduction improves the reaction yield, rate, and reproducibility. The acetic anhydride is added immediately prior to hydrogen introduction so that the acetic anhydride does not have time to react with the HBIW to form N-benzylacetamide which acts as a catalyst poison, which is a major contributor to incomplete or low yield reactions. N-benzylacetamide is formed by the acid catalyzed decomposition of HBIW to yield "free" benzyl amine followed by acetylation of the benzyl amine by acetic anhydride. This reaction occurs slowly once the reaction mixture is together. To minimize this unwanted reaction, the co-solvent and HBIW are preferably placed in the reaction vessel first, followed by the bromine source. The contents are thoroughly mixed and placed under a nitrogen atmosphere. The acetic anhydride and the washed palladium catalyst are then added quickly, followed immediately by hydrogen introduction. Once the acetic anhydride is added to the HBIW, the hydrogen should be added rapidly to inhibit unwanted side reactions.

Once hydrogen is introduced into the reaction vessel, the HBIW is converted to TADB, which precipitates onto the palladium hydrogenolysis catalyst and is easily recovered by filtration. The co-solvent assists in providing complete precipitation. After the hydrogenolysis is complete, the product and catalyst are filtered from the liquid phase and washed with a solvent, such as denatured ethanol, methanol, or isopropanol. The solvent is preferably miscible with the DMF, acetic anhydride, and acetic acid so that these compounds can later be removed from the TADB product. The solvent is also preferably immiscible with the desired TADB product so that the TADB is not dissolved and washed away with the solvent. It is also important that the solvent have not effect on the subsequently hydrogenolysis reaction.

The filtered and washed TADB is sufficiently pure for a second hydrogenolysis reaction in which the TADB product and catalyst are reacted to form TADH, as depicted as follows:



- 5 A suitable catalyst and solvent for the second hydrogenolysis reaction are $\text{Pd}(\text{OAc})_2$ and acetic acid, respectively. The second hydrogenolysis reaction is slower than the first hydrogenolysis reaction, due to the reduced activity of the last two benzyl groups of the TADB towards hydrogenation. This second hydrogenolysis step is preferably performed in the absence of
- 10 formic acid or other acid to prevent the formation of TADF or equivalent compounds.

The catalyst is removed by filtration, and the product is recovered by evaporation of the volatile solvents. The catalyst may be recycled and used again in the process or it may be reprocessed by the catalyst manufacturer.

- 15 The TADH product thus obtained is of a purity suitable for direct use in the nitration reaction to produce HNIW.

- The HNIW can be thereafter crystallized to ϵ -polymorph HNIW in accordance with the technique disclosed in allowed U.S. Patent No. 5,874,574 the complete disclosures of which are incorporated herein by
- 20 reference. (According to this U.S. patent, a quantity of CL-20 is dissolved in a solution containing a CL-20 solvent, such as ethyl acetate, and water. The resulting mixture consists of two liquid phases: an aqueous phase and a wet solvent phase. The pH of the aqueous phase can be tested and adjusted at this point as desired. The CL-20 is dissolved in the wet solvent phase, which

is dried by removing a solvent/water azeotrope according to conventional distillation techniques, thereby forming a dry solvent phase containing the CL-20. A low density non-polar CL-20 non-solvent, such as hexane, cyclohexane, heptane, octane, benzene, toluene, xylene, mineral oil, petroleum ethers, and ligroin, is added to the dry CL-20 solvent phase to cause crystallization of ϵ -polymorph CL-20. The low density nonpolar non-solvent preferably has a density less than water. The CL-20 crystals are then separated from the non-solvent and the solvent by adding sufficient water to displace the non-solvent and the solvent from the surface of the ϵ -CL-20 crystals. In this fashion, ϵ -polymorph CL-20 is made wet for later handling, packaging, and shipping. The ratio of water to CL-20 should typically range from 1:7 to 3:1, by volume. More water can be easily used in the system, but larger quantities of water will require larger equipment for separating and recycling the water. The wet CL-20 is collected and the CL-20 non-solvent, CL-20 solvent, and excess water are removed to separate and recycle the individual solvents.)

The conversion to nitramine as reported and claimed herein is determined by NMR standards by the procedure detailed above in the Summary and the Example below. However, it is to be understood that other standards for determining nitramine conversion exist, although such other standards may alter the appropriate timing for obtaining 99% conversion and, therefore, should not be used in determining the literal and equivalent scope of the appended claims. One alternative, unclassified standard for determining HNIW purity was developed pursuant to a Standardization Agreement between the North Atlantic Treaty Organization (NATO) and the Military Agency for Standardization (MAS). This standard is STANAG4566. Under this Standardization Agreement, chemical purity is determined by using high performance liquid chromatograph (HPLC) equipped with a 226 nm UV detector and an integrator or computer link up to a data acquisition. Generally, a conversion of 97% (as measured by the STANAG4566) can be achieved in less than 30 minutes, preferably in less than 20 minutes.

The unexpected superior results obtained by practicing the present invention are manifested by the following experiments, which are presented for the purpose of explanation and are not to be considered limiting on the scope of the invention.

5

EXAMPLES

Examples 1-5

1 gram of TADH substrate was cooled with an ice bath to 6°C. A mixed acid solution of $\text{H}_2\text{SO}_4/\text{HNO}_3$ (in the concentrations specified in the Table below) at 25°C was added to the ice bath. The mixture was then heated in a bath having a temperature of 95°C, and samples were removed and tested for nitramine conversion in 5 minute intervals as specified in the Table. The results are reported in the Table below.

Table

	H ₂ SO ₄ (ml)	HNO ₃ (ml)	Time (min)	Conversion to Nitramine
Example 1	1	9	20	72
	1	9	25	91
	1	9	30	91
	1	9	35	97
	1	9	40	98
Example 2	2	8	15	92
	2	8	20	100
	2	8	25	100
	2	8	30	100
	2	8	35	100
	2	8	40	100
Example 3	3	7	10	100
	3	7	15	100
	3	7	20	100
	3	7	25	100
	3	7	30	100
	3	7	35	100
	3	7	40	100
Example 4	4	6	5	91
	4	6	10	91
	4	6	15	88
	4	6	20	100
	4	6	25	100
	4	6	30	100
	4	6	35	100
	4	6	40	100
Example 5	5	5	10	71
	5	5	15	89
	5	5	20	92
	5	5	30	98

Analysis of the samples for conversion to nitramine was generally performed in accordance with the following procedures. A small amount (ca. 80 mg) of air dried product was dissolved in D6-acetone and was recorded with ¹H spectrum on a 300MHz Varian XL300 nmr spectrometer. HNIW has two peaks at about 8.23 and 8.36 ppm, with an integral ratio of 1:2. The extent of reaction or conversion was assessed by taking the ratio of the peak

areas of the smaller HNIW peak to the largest of any impurity peak observed between 7 and 9 ppm.

As shown from these results, a mixed acid ratio of $\text{HNO}_3:\text{H}_2\text{SO}_4$ of 7:3 produced a product having approximately nitramine conversion within 10 minutes. By contrast, a mixed acid ratio of $\text{HNO}_3:\text{H}_2\text{SO}_4$ of 9:1 did not produce a product having a 99% nitramine conversion within the 40 minutes of testing. A mixed acid ratio of 5:5 did not produce a product having 99% nitramine conversion within 30 minutes of testing. Mixed acid ratios of $\text{HNO}_3:\text{H}_2\text{SO}_4$ of 8:2 and 6:4 each took about 20 minutes to undergo 99% nitramine conversion.

Example 6: Preparation of HBIW

To a mixture of 12 kg of DMF and 70 kg (686 moles) of acetic anhydride in a 75 gallon stirred autoclave (steel reactor) were added 43.2 kg (61 moles) of HBIW, 0.781 (7.4 moles) of bromobenzene, and 4.63 kg of a 55.3% moisture 10% palladium on carbon catalyst (dry weight of catalyst was 2.07 kg). The vessel was purged four times with hydrogen. During the purges, the temperature of the reactor rose from 21.3°C to 25.2°C. The reaction was then stirred under 50 psi pressure of hydrogen introduced into the reaction mixture via a sparge ring. Over the next 30 minutes, the reaction temperature rose to 51.4°C and cold water was then circulated through the jacket of the flask to control the exotherm. Approximately 140 moles of hydrogen (based on pressure drop in the hydrogen tank) were consumed during this period not counting any hydrogen consumed during the purges. Over the next 1.5 hours, another 120 moles of hydrogen were consumed with the reaction temperature then at 43.1°C (cold water was stopped circulating when the reaction temperature dropped below 35°C). The reaction was allowed to stir an additional 21 hours during which time another 40 moles of hydrogen were consumed (total of 300 moles versus a theoretical 250 moles for the reaction). The reactor was purged three times with nitrogen then the reaction mixture was filtered. The solids were washed with roughly 130 liters

of denatured ethanol to afford the desired product along with palladium catalyst slightly moist with ethanol and trace amounts of DMF as a gray solid. In a total of three reactions ran as described above, a total of 85.7 kg (82-85% yield) of the product mixture were obtained.

5

Example 7: Preparation of TADH

In a Parr apparatus was placed 6g of HBIW, 200ml acetic anhydride, 1.5g Pearlman's palladium hydroxide on charcoal (20% Pd) and .17g bromobenzene. After flushing the apparatus with hydrogen, the pressure of hydrogen was increased to 50psi for 18 hours. After this time the catalysts/product mixture was removed by filtration, and extracted with twice with 80ml boiling chloroform. The extract was concentrated and triturated with acetonitrile to give TADB. 3.67g of this TADB, 1.6g Pd(OAc)₂, and 150ml acetic acid were placed in a Parr apparatus. After flushing the apparatus with hydrogen, the pressure of hydrogen was increased to 3.455 kgf/cm² for 15 hours. After this time, the reaction mixture was filtered and the mother liquor evaporated to give a solid which was washed with 100ml ethyl acetate to yield 1.67g of TADH.

20 The foregoing detailed description of the preferred embodiments of the invention has been provided for the purpose of explaining the principles of the invention and its practical application, thereby enabling others skilled in the art to understand the invention for various embodiments and with various modifications as are suited to the particular use contemplated. This description is not intended to be exhaustive or to limit the invention to the precise embodiments disclosed. Modifications and equivalents will be apparent to practitioners skilled in this art and are encompassed within the spirit and scope of the appended claims.

WE CLAIM:

1. A process for the nitrolysis of 2,6,8,12-tetraacetyl-2,4,6,8,10,12-hexaazatetracyclo-[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("TADH") to form 2,4,6,8,10,12-hexanitro-2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("HNIW"), said process comprising treating said TADH with a mixed acid comprising one or more nitronium ion sources and one or more strong acids for generating nitronium ions from said source and forming HNIW, wherein said nitronium ion source and strong acid are present at a volumetric ratio of about 7:3.
2. A process according to claim 1, wherein said volumetric ratio is selected and said TADH is present in such an amount that, in the event that said treating step is conducted at a temperature of 85°C, said forming of the HNIW attains a conversion to nitramine of at least a 99% within 20 minutes.
3. A process according to claim 1, wherein said volumetric ratio is selected and said TADH is present in such an amount that, in the event that said treating step is conducted at a temperature of 85°C, said forming of the HNIW attains a conversion to nitramine of at least a 99% within 10 minutes.
4. A process according to claim 3, wherein said process is conducted at 85°C and said forming of the HNIW attains a conversion to nitramine of at least a 99% within 10 minutes.
5. A process according to claim 3, wherein a ratio of said TADH in grams to said mixed acid in milliliters is in a range of from about 1:7 to about 1:30.

6. A process according to claim 3, wherein a ratio of said TADH in grams to said mixed acid in milliliters is in a range of from about 1:7.5 to about 1:10.

5

7. A process according to claim 3, wherein a ratio of said TADH in grams to said mixed acid in milliliters is about 1:8.

8. A process according to claim 1, wherein said process is
10 continuous.

9. A process for the nitrolysis of 2,6,8,12-tetraacetyl-2,4,6,8,10,12-hexaazatetracyclo-[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("TADH") to form 2,4,6,8,10,12-hexanitro-2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]-
15 dodecane ("HNIW"), said process comprising treating said TADH with a mixed acid comprising HNO₃ and H₂SO₄ and forming HNIW, wherein a volumetric ratio of HNO₃ and H₂SO₄ is in a range of from about 6:4 to about 8:2.

10. A process according to claim 9, wherein said volumetric ratio is
20 selected and said TADH is present in such an amount that, in the event that said treating step is conducted at a temperature of 85°C, said forming of the HNIW attains a conversion to nitramine of at least a 99% within 10 minutes.

11. A process according to claim 10, wherein said volumetric ratio is
25 about 7:3.

12. A process according to claim 10, wherein said process is conducted at 85°C.

13. A process according to claim 10, wherein a ratio of said TADH in grams to said mixed acid in milliliters is in a range of from about 1:7 to about 1:30.

14. A process according to claim 10, wherein a ratio of said TADH in grams to said mixed acid in milliliters is in a range of from about 1:7.5 to about 1:10.

15. A process according to claim 10, wherein a ratio of said TADH in grams to said mixed acid in milliliters is about 1:8.

16. A process according to claim 9, wherein said process is continuous.

17. A process for the nitrolysis of 2,6,8,12-tetraacetyl-2,4,6,8,10,12-hexaazatetracyclo-[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("TADH") to form 2,4,6,8,10,12-hexanitro-2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("HNIW"), said process comprising:

introducing said TADH and a mixed acid into a first cooling vessel to dissolve said TADH and form a solution, said mixed acid comprising one or more nitronium ion sources and one or more strong acids for generating nitronium ions from said source, wherein said nitronium ion source and strong acid are present at a volumetric ratio of about 7:3;

transferring said solution to a heated reaction vessel for nitrolysis of

said TADH with said mixed acid and forming said HNIW; and
transferring said solution to a second cooling vessel to cool said HNIW.

18. A process according to claim 17, wherein said volumetric ratio is
5 selected and said TADH is present in such an amount that, in the event that
said nitrolysis is conducted at a temperature of 85°C, said forming of the
HNIW attains a conversion to nitramine of at least a 99% within 20 minutes.

19. A process according to claim 17, wherein said volumetric ratio is
10 selected and said TADH is present in such an amount that, in the event that
said nitrolysis is conducted at a temperature of 85°C, said forming of the
HNIW attains a conversion to nitramine of at least a 99% within 10 minutes.

20. A process according to claim 19, wherein said first and second
15 cooling vessels are operated in a range of from about 0°C to about 20°C.

21. A process according to claim 19, wherein said heated reaction
vessel is operated at a temperature of about 85°C.

22. A process according to claim 19, wherein a ratio of said TADH in
20 grams to said mixed acid in milliliters is in a range of from about 1:7 to about
1:30.

23. A process according to claim 19, wherein a ratio of said TADH in
25 grams to said mixed acid in milliliters is in a range of from about 1:7.5 to about
1:10.

24. A process according to claim 19, wherein a ratio of said TADH in grams to said mixed acid in milliliters is about 1:8.

5 25. A process according to claim 17, wherein said process is continuous.

26. A process for the nitrolysis of 2,6,8,12-tetraacetyl-2,4,6,8,10,12-hexaazatetracyclo-[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("TADH") to form
10 2,4,6,8,10,12-hexanitro-2,4,6,8,10,12-hexaazatetracyclo[5.5.0.0^{5,9}.0^{3,11}]-dodecane ("HNIW"), said process comprising:

introducing said TADH and a mixed acid into a first cooling vessel to dissolve said TADH and form a solution, said mixed acid comprising comprising HNO₃ and H₂SO₄, wherein a volumetric ratio of HNO₃ and H₂SO₄
15 is in a range of from about 6:4 to about 8:2;

transferring said solution to a heated reaction vessel for nitrolysis of said TADH with said mixed acid and forming said HNIW; and
transferring said solution to a second cooling vessel to cool said HNIW.

20 27. A process according to claim 26, wherein said volumetric ratio is selected and said TADH is present in such an amount that, in the event that said nitrolysis is conducted at a temperature of 85°C, said forming of the HNIW attains a conversion to nitramine of at least a 99% within 10 minutes.

25 28. A process according to claim 27, wherein said volumetric ratio is about 7:3.

29. A process according to claim 27, wherein said first and second cooling vessels are operated in a range of from about 0°C to about 20°C.

30. A process according to claim 27, wherein said heated reaction
5 vessel is operated at a temperature of about 85°C.

31. A process according to claim 27, wherein a ratio of said TADH in grams to said mixed acid in milliliters is in a range of from about 1:7 to about 1:30.


10

32. A process according to claim 27, wherein a ratio of said TADH in grams to said mixed acid in milliliters is in a range of from about 1:7.5 to about 1:10.

15

33. A process according to claim 27, wherein a ratio of said TADH in grams to said mixed acid in milliliters is about 1:8.

34. A process according to claim 26, wherein said process is continuous.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 September 2000 (08.09.2000)

PCT

(10) International Publication Number
WO 00/52011 A3

(51) International Patent Classification⁷: C07D 487/22, C07B 43/02

(21) International Application Number: PCT/US00/03784

(22) International Filing Date: 15 February 2000 (15.02.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/120,187 16 February 1999 (16.02.1999) US

(71) Applicant: CORDANT TECHNOLOGIES, INC.
[US/US]; Suite 1600, 15 West Temple, Salt Lake City, UT 84101-1532 (US).

(72) Inventors: SANDERSON, Andrew, John; 2711 North, Mountain Road, North Ogden, UT 84414 (US). WARNER, Kirstin; 1175 Canyon Road #59, Ogden, UT 84404 (US). WARDLE, Robert, B.; 1630 North, 1770 East, Logan, UT 84321 (US).

(74) Agents: COLTON, Kendrew, H. et al.; Pillsbury Madison & Sutro, LLP, 1100 New York Avenue, NW, Washington, DC 20005 (US).

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— With international search report.

(88) Date of publication of the international search report:
11 January 2001

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 00/52011 A3

(54) Title: PROCESS FOR MAKING 2,4,6, 8,10,12- HEXANITRO- 2,4,6,8,10, 12- HEXA AZATETRACYCLO [5.5.0. 0⁵.0³.1¹] -DODECANE

(57) Abstract: In this process 2,6,8, 12-tetraacetyl- 2,4,6,8, 10,12-hexaazatetracyclo- [5.5.0.05, 903,11]-dodecane ("TADH") is subjected to nitrolysis in the presence of a mixed acid to form HNIW. The mixed acid comprises at least one nitronium ion source (preferably nitric acid) and at least one strong acid (preferably sulfuric acid) capable of generating a nitronium ion from the source. The ratio of nitronium ion source to strong acid and the amount of TADH used are selected so that, in the event that the nitrolysis reaction is carried out at 85 °C, 99 % nitramine conversion will occur within ten minutes.

INTERNATIONAL SEARCH REPORT

International Application No:
PCT/US 00/03784

A. CLASSIFICATION OF SUBJECT MATTER
C07D487/22,C07B43/02

According to International Patent Classification (IPC) or to both national classification and IPC⁷

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C07D,C07B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X, P	EP 0919556 A1 (ASAHI KASEI KOGYO KABUSHIKI KAISHA) 02 June 1999, claims, page 5, lines 33-48, page 7, lines 31-53, page 10, lines 36-51, examples 1,4,6.	1
P, A	---	2-34
A	EP 0753519 A1 (ASAHI KASEI KOGYO KABUSHIKI KAISHA) 15 January 1997, claims, page 12, lines 22-57. -----	1-34

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

31 August 2000

Date of mailing of the international search report

11. 10. 2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

WENIGER

ANHANG

Zum internationalen Recherchenbericht über die internationale Patentanmeldung Nr.

In diesem Anhang sind die Mitglieder der Patentfamilien der im obengenannten internationalen Recherchenbericht angeführten Patentedokumente angegeben. Diese Angaben dienen nur zur Unterrichtung und erfolgen ohne Gewähr.

ANNEX

To the International Search Report to the international Patent Application No.

PCT/US 00/03784 SAE 288717

This annex lists the patent family members relating to the patent documents cited in the above-mentioned search report. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

ANNEXE

Au rapport de recherche international relatif à la demande de brevet international n°

La présente annexe indique les membres de la famille de brevets relatifs aux documents de brevets cités dans le rapport de recherche international visée ci-dessus. Les renseignements fournis sont donnés à titre indicatif et n'engagent pas la responsabilité de l'Office.

Im Recherchenbericht angeführte Patentedokumente Patent document cited in search report Document de brevet cité dans le rapport de recherche			Datum der Veröffentlichung Publication date Date de publication		Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets		Datum der Veröffentlichung Publication date Date de publication	
EP	A1	919556	02-06-1999		AU	A1	37830/97	25-02-1998
					CN	A	1227556	01-09-1999
					JP	B2	3034054	17-04-2000
					WO	A1	9805666	12-02-1998
EP	A1	753519	15-01-1997		CN	A	1241567	19-01-2000
EP	A4	753519	07-05-1997		CN	A	1241568	19-01-2000
EP	B1	753519	17-05-2000		CN	A	1148388	23-04-1997
					CN	A	1245170	23-02-2000
					CN	B	1052483	17-05-2000
					DE	C0	69608359	21-06-2000
					RU	C1	2125572	27-01-1999
					WO	A1	9623792	08-08-1996
					JP	B2	2844125	06-01-1999